



66 Marine Street, Farmingdale, NY 11735 - P: 877-683-8086 - F: 631-229-8000 - <https://www.mileslubricants.com/>

MILES SB COMP OIL PLUS

Synthetic Blend Air Compressor Lubricant

MILES SB COMP OIL PLUS synthetic blend compressor lubricant is designed for Rotary Screw, Reciprocating and Vane air compressors. This premium lubricant gives outstanding service — even in moderately severe operating conditions. With enhanced oxidative and thermal stability, MILES SB COMP OIL PLUS is designed to provide 4,000–6000 hours of service.

ATTRIBUTES

- 4,000–6,000 hours of oil life at 100°C discharge temperature
- Enhanced thermal and oxidative stability
- Protects against wear, rust and corrosion
- Resists water contamination
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

MILES SB COMP OIL PLUS Grades	32	46	68	100
Viscosity cSt @ 40°C	31	45	69	100
Viscosity cSt @ 100°C	5.3	6.7	9.0	11.8
Flash Point °F (°C)	428 (220)	442 (228)	453 (234)	510 (265)
Demulsibility	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0